



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DW-4715CU0111

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Apator Powogaz S.A. ul. K. Janickiego 23/25, PL-60-542 Poznan
Distributor <i>Vertreiber</i>	Apator Powogaz S.A. ul. K. Janickiego 23/25, PL-60-542 Poznan
Product Category <i>Produktart</i>	flow meters: Water flowmeters (4715)
Product Description <i>Produktbezeichnung</i>	ultrasonic water meter
Model <i>Modell</i>	ULTRIMIS-W
Test Reports <i>Prüfberichte</i>	supplement test: WZ 001/20+WZ 002/20 from 28.10.2020 (TZW) type testing: WZ 005/17 from 05.04.2019 (TZW) KTW testing: K-281196-17-Bs/st from 14.02.2017 (WHY) hygienic testing: W-291948e-17-SI/to from 24.11.2017 (WHY) KTW testing: K-278100-16-Ko from 24.11.2016 (WHY) hygienic testing: W-286149-17-SI/to from 13.06.2017 (WHY)
Test Basis <i>Prüfgrundlagen</i>	DVGW W 421 (01.05.2009) UBA METALLE (21.11.2018) UBA ELASTOM (16.03.2016) UBA KTW (07.03.2016) DVGW W 270 (01.11.2007)
Date of Expiry / File No. <i>Ablaufdatum / Aktenzeichen</i>	05.04.2024 / 20-0330-WNR

70208-04-A-DE

26.11.2020 Fk A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-05

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Type Typ	Technical Data Technische Daten	Remarks Bemerkungen
UL2,5	pressure rating: PN 16 nominal diameter: DN 15 flow capacity: 2,5 m ³ /h	length: 110 mm
UL2,5	pressure rating: PN 16 nominal diameter: DN 15 flow capacity: 2,5 m ³ /h	length: 80 mm
UL2,5	pressure rating: PN 16 nominal diameter: DN 15 flow capacity: 2,5 m ³ /h	length: 115 mm
UL2,5	pressure rating: PN 16 nominal diameter: DN 15 flow capacity: 2,5 m ³ /h	length: 115 mm
UL2,5	pressure rating: PN 16 nominal diameter: DN 15 flow capacity: 2,5 m ³ /h	length: 165 mm
UL4	pressure rating: PN 16 nominal diameter: DN 20 flow capacity: 4,0 m ³ /h	length: 130 mm
UL4	pressure rating: PN 16 nominal diameter: DN 20 flow capacity: 4,0 m ³ /h	length: 105 mm
UL4	pressure rating: PN 16 nominal diameter: DN 20 flow capacity: 4,0 m ³ /h	length: 115 mm
UL4	pressure rating: PN 16 nominal diameter: DN 20 flow capacity: 4,0 m ³ /h	length: 190 mm
UL6,3	pressure rating: PN 16 nominal diameter: DN 25 flow capacity: 6,3 m ³ /h	length: 260 mm
UL6,3	pressure rating: PN 16 nominal diameter: DN 25 flow capacity: 6,3 m ³ /h	length: 165 mm
UL10	pressure rating: PN 16 nominal diameter: DN 32 flow capacity: 10 m ³ /h	length: 260 mm
UL10	pressure rating: PN 16 nominal diameter: DN 32 flow capacity: 10 m ³ /h	length: 260 mm
UL16	pressure rating: PN 16 nominal diameter: DN 40 flow capacity: 16 m ³ /h	length: 300 mm
UL 25	pressure rating: PN 16 nominal diameter: DN 50 flow capacity: 25 m ³ /h	length: 200 mm and 300